

The new C1025WS

A warewashing solution with something new to offer. The ever popular C range now has a passthrough model which includes an internal, automatic water softener as standard.

The C range is renowned within the catering industry for performance and durability at a great price.

Now there is a passthrough model in the range with an internal, automatic water softener as standard.

And still great value for money.



Technical Specifications C1025WS

Physical

Width	mm	716
Width (excluding handle)	mm	635
Height	mm	1449/1509
Height (hood open)	mm	1885/1945
Depth	mm	740
Depth (inc. handle)	mm	810
Weight	kg	120
Cycle times - adjustable	secs	90-12-180

Racks

Size	mm	500
Glasses per rack (pint)		25
Max usable height	mm	400
Racks supplied		2
Racks per hour		60-30-20

Water

Water inlet		3/4"
Waste outlet (grav/pump)	mm	35/25
Pressure min	bar	2
Pressure max	bar	4
Consumption per cycle	litres	3
Wash tank capacity	litres	20
Wash tank temp	deg C	45 to 65
Rinse boiler capacity	litres	7
Rinse boiler temp	deg C	65 to 90

Electric

Voltage	V	240/415
Phase		Single/three
Current (phase)	amps	20(1), 10(3)
Wash pump	kw	0.6
Wash tank element	kw	1.4
Rinse tank element	kw	6.0
Total loading (phase)	kw	4.6(1), 6.8(3)*

Features

Rinse aid pump	Peristaltic
Detergent pump	Peristaltic
Drain pump	Standard
Internal Break-Tank	Yes
Automatic Water Softener - ECS (Continuous)	Yes

*Available 6.6 kW (30 amps) single phase

General Features

- Internal, automatic water softener
- 2 year warranty
- C1010 with fitted type 'A' air gap breaktank
- Simple electro-mechanical push button controls
- Proven electronic time and temperature control
- 2 cycle times
- Corner or straight through inlet tabling configurations
- Built-in rinse aid dispenser
- Surface tray filter – to prevent debris from contaminating wash water
- Self draining wash pump – to reduce health risk from bacteria build up
- Up to 1080 plates per hour
- Superbly designed internal surfaces – simple to keep clean



Oaktree Court Business Centre
Mill Lane, Neston, Wirral, Cheshire CH64 8TP

Tel: 0333 123 2450

In the event of further technical development we reserve the right to alter our design, specification and price without notice.